



CBEFFIO2.8-11GR/WH

DUAL VOLTAGE IR DOME

OPTIONAL ACCESSORIES

350-008/007 350-006/005 350-028/029

ALSO AVAILABLE IN WHITE

The ideal all rounder

- Dual Voltage 12VDC/24VAC ideal solution for specific environments
- Sony Effio-E DSP 700TVL
- Varifocal 2.8-11mm
- Day/ Night 25m IR range
- IP66 Vandal resistant construction
- Available in White or Grey



Model	CBEFFIO2.8-11GR	CBEFFIO2.8-11WH
Product Code	100-058	100-059
Image sensor / DSP	1/3" SONY Super HAD II CCD & Effio-E DSP	
Signal system	PAL	
Pixels	795(H) x 596(V)	
Effective Pixels	752(H) x 582(V)	
Resolution	Colour : 700TV lines (Min.), B/W : 720TV lines (Min.)	
Varifocal Range	f2.8mm~11mm	
Digital WDR	Off/On (0-63 level adjustments)	
White balance	ATW(1800°K ~ 10,500°K)	
Scan system	2 : 1 Interlace	
O.S.D	Built In	
Sync system	Internal	
Minimum illumination	Colour 0.3lux, Monochrome 0Lux (IR on)	
Electronic shutter	Auto/Manual(1/50sec ~ 1/120,000sec)	
S/N ratio	≥52dB	
Day & Night	Colour/B&W/ Auto	
Illumination	5mm LED x 36 Pcs 850nm	
IR distance	25m	
Connections	Polarity Marked Screw Terminal Jack / Standard BNC	
Power requirements	12VDC / 24VAC @ 450mA(Max)	
Construction	Die cast anodized aluminium, IP66	
Dimensions	94mm Dia X 64mm L	
Weight	820g	
Operation temp.	-10°C, +50°C	